



” The exclusive  
POS System

Specifications – P2100

- Robust panel system with resistive or PCAP touch monitor and stand
- Without fan: silent and reliable
- Hospitality professional with IP64-protected front panel
- Efficient Intel processor at up to 2.0 GHz, and up to 8 GB RAM

		P2100
<b>System</b>	CPU	Intel Celeron J1900, Quad-Core, 2.0 GHz (fanless)
	System memory	4 GB SO-DIMM, DDR3L, 1333 MHz, max. 8 GB (1 bank)
	Chipset	BayTrail platform
	Compact Flash	CFlash card support
	Hard disk drive	120 GB SSD, HDD optional
	Audio	On-board
	Supported operating systems	Windows 10 / Linux
	Housing	Aluminium
<b>Display</b>	Graphics chip	Intel HD Graphics
	LCD screen size	38.1 cm (15")
	Maximum resolution	1024 x 768 pixels
	Brightness	350 nits
	Touch screen	5-wire resistive, Projected Capacitive (optional)
Tilt angle	0 to 90°	
<b>Interfaces</b>	USB	3x USB 2.0; 1x USB 3.0
	Serial/COM	3x DB9, 1x RJ45 (powered 5 V / 12 V available)
	Parallel	Available on demand
	LAN	1x RJ45 10/100/1000 Base-T
	VGA	1x
	PS/2	1x
	Cash drawer port	1x RJ11 (12 V)
Audio	Line-out, mic-in, speaker	
<b>PSU</b>	Power adapter	90 watts
<b>Other</b>	Dimensions (WxDxH)	323.6 x 264.2 x 368 mm
	Weight	7.6 kg
	Operating temperature	0 to 40 °C
	Certification	CE, FCC, RoHS, IP64 (front panel)
	Mount	VESA 100 mm
<b>Options</b>	Magnetic stripe reader	Choice of MSR (track 1, 2, 3), MSR + iButton reader, MSR + smart card reader + iButton reader, MSR + smart card reader + fingerprint reader
	Customer display	VFD, 2 x 20 characters (integrated or pole type)
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") screen size
	Barcode scanner	1D or 2D barcode scanner (optional RFID capability)
	Waiter lock	iButton (optional RFID capability), Addimat (RS232)
	RFID	13.56 MHz (MIFARE), 125KHz
	Colour	Black, white
UPS	Up to 1 hour battery backup	

Your partner